

# WIDEBAND SLOT ANTENNA FOR MIMO SYSTEMS

Apinya Innok, Watcharaphon Naktong and Nuchanart Fhaphiem

Department of Telecommunications Engineering, Faculty of Engineering and Architecture,

Rajamangala University of Technology Isan, Muang, Nakhon Ratchasima, Thailand

744, Nai Muang, Muang, Nakhon Ratchasima, Thailand

Email: apinya\_in@hotmail.com

## ABSTRACT

This paper investigates into the performance of slot antenna for MIMO systems for increasing bandwidth technique. From another research, a large size and low bandwidth of traditional antenna which cannot put into wireless communication device are defects of antenna. The defect can be overcome by increase of bandwidth was adjusted by using L-shape slot etching on the rectangular stub and adding double I shaped stub tuning on ground plane for matching impedance 50 ohm. Then, this paper uses array the adjustable antenna 2 element for increasing efficiency on MIMO system. The antenna structure was designed and fabricated on print circuit board (PCB) with FR4. The operational parameters and characteristics of the proposed antenna were determined by using the simulation: Finite-difference time-domain. The simulation results indicated that the reflection coefficient of proposed antenna was reduced less than -10 dB. The proposed antenna is capable of WLAN (IEEE 802.11b/g)/WiMAX (IEEE 802.16e) applications. The simulated bandwidth of proposed antenna is 53.7% (1.88 - 3.26GHz) which was pressed with the average gain value of 5.65 dBi.

## 1. INTRODUCTION

Presently, the requirement of the wireless local area network (WLAN) based on IEEE 802.11 b/g/n (Parkash D., et al., 2010), (Zhu C., et al., 2012), (Kalraiya S., et al., 2014) and worldwide interoperability for microwave access (WiMAX) based on IEEE 802.16e are becoming increasingly unsustainable in both developing and developed countries. Therefore, the wireless developed organization is considered WLAN for further wireless communication. So for in literature, the antenna structures such as microstrip antenna, monopole antenna or slot antenna have been studied as adjusting structure. Many works have been proposed the structure of rectangular shape to fix in each frequency (Jearapraditkul P., et al., 2008), (Krishna D., et al., 2008). Some studies have been added rectangular waveguide to increase bandwidth and gains (Chaiboon

P., et al., 2011), (Naktong W., et al., 2014), (Kaewchan B., et al., 2010), (Tunti-A-longkarn P. et al., 2011) (Zhang L., et al., 2013), (C. A. Balanis, 1982). Therefore, this paper applies the rectangular antenna using L-shape slot, double I-shaped stub tuning on ground plane and adding rectangular waveguide for using WLAN and WiMAX systems.

## 2. STRUCTURE AND DESIGNING PRINCIPLES

### 2.1 Antenna Structure

In this paper, the proposed antenna was developed from rectangular slot antenna. The increasing of bandwidth from original antenna was studied by using L-shape slot etching on the rectangular stub, adding double I shaped stub tuning on ground plane and adding rectangular waveguide as shown in Fig.1 and 2, respectively. The antenna structure was designed and fabricated on print circuit board (PCB) with FR4 base with the dielectric constant of 4.3 and the thickness ( $h$ ) of 0.764 mm. by the proposed antenna size as  $W1 = 67$  mm and  $L1 = 50$  mm. The tuning parameters were width:  $W1 = 67$  mm,  $W2 = 63$  mm,  $W3 = 22$  mm and  $W4 = 1$  mm,  $W5 = 12$  mm,  $W6 = 2.5$  mm and  $W7 = 4$  mm,  $g = 1.3$  mm, Length:  $L1 = 50$  mm,  $L2 = 36$  mm,  $L3 = 38$  mm,  $L4 = 14$  mm,  $L5 = 6$  mm,  $L6$  and  $L7 = 1$  mm,  $t = 0.017$  mm.




Fig. 1 Model of antenna structure.




Fig. 2 Waveguide for applying antenna.

Table 1. All parameters of antenna.

Width (mm)		Length (mm)	
$W_1$	67	$L_1$	50
$W_2$	63	$L_2$	36
$W_3$	22	$L_3$	38
$W_4$	1	$L_4$	14
$W_5$	12	$L_5$	6
$W_6$	2.5	$L_{6,7}$	1
$W_7$	4	$t$	0.017
$g$	1.3	$h$	0.764




Fig. 3 Simulation results of reflection coefficient ( $S_{11}$ ) when adding waveguide.




Fig. 4 Simulation results of reflection coefficient when adjusting  $W_6$ , and  $W_7$ .




Fig. 5 Simulation results of reflection coefficient when adjusts  $W_4$ ,  $W_5$ ,  $L_5$  and  $L_6$




Fig. 6 Simulation results of Gain (dBi).

Table 2. The simulated results.

Type	BW (GHz)	Center Freq.(GHz)	Gain (dBi)	BW (%)
Type 1	2.61 - 2.25	2.43	3.04	14.81
	3.78 - 3.15	3.46	3.16	18.20
Type 2	1.76- 3.38	2.57	5.31	63.03
Type 3	1.85- 3.51	2.68	5.65	61.94

## 2.2 Simulation Results for Antenna Structure

The operational parameters and characteristics of the proposed antenna were determined by using the simulation: Finite-difference time-domain. The sizes of both stub tuning are calculated at 2.45GHz. All parameters were adjusted unit antenna reached the maximum efficiency. The simulated all parameter of antenna shown in Table 1.

Based on rectangular antenna structure, the antenna tuning was separated into 3 steps. First, the rectangular antenna structure (Type 1) was added rectangular waveguide (Type 2). The results reveal that the proposed antenna adding waveguide offers a reflection coefficient lower than the antenna without waveguide as shown in Fig.3.




Fig. 7 Array antenna for applying MIMO systems.




Fig. 8 Simulation results of reflection coefficient ( $S_{11}$ ).




Fig. 9 Simulation results of isolation ( $S_{12}$ ,  $S_{21}$ ).

In the second step, the antenna structure was adjusted by etching I-shaped slot on radiation patch under various tuning parameter  $W_6$  (from 0, 1.5, 2.5, 3.5 and 4.5 mm) whereas parameter  $L_7$  value was fixed at 1 mm. After tuning, the best value of  $W_6$  was 2.5 mm at constant value  $L_7 = 1$  mm. The bandwidth of tuning antenna occurred in frequency range was 1.75 – 3.28 GHz (60.95%). The reflection coefficient was less than -10 dB. But, the impedances bandwidth at 2.45 GHz is 36.97-j6.95 OHM. It has not nearly 50 OHM. Therefore, the tuning of antenna structure in the third step was requested.

In third step, the tuning parameter  $W_5$  started at 6 mm then stepwise increased to 9, 12, 14 and 16 mm while parameter  $W_4$  was fixed at 1 mm. After tuning, it was found that the appropriate value of  $W_5$  was 8 mm at constant value  $W_4 = 1$  mm. Then, the tuning parameter  $L_5$  started at 2 mm then stepwise increased to 4, 6, 8 and 10 mm while parameter  $L_6$  was fixed at 1 mm. After tuning, it was found that the appropriate value of  $L_5$  was 6 mm at constant value  $L_6 = 1$  mm.




Fig. 10 Simulation results of radiation pattern at 2 GHz, 2.5 GHz and 3 GHz.

Finally, the bandwidth of tuning antenna was 1.85 – 3.51 GHz (61.94%). The impedances bandwidth is nearly 50 OHM. According to simulation results, the reflection coefficient in Fig. 5 was lower than Fig.4 when L shaped slot tuning was added. The simulation results indicated that the reflection coefficient of proposed antenna was reduced lower than -10 dB. The simulation results of Gain (dBi) as shown in Fig.6. The simulated all parameters (Frequency, Gain and Bandwidth) of antenna with 3 types as shown in Table 2. However, it is impossible to fully know the channel in a real fading environment. Thus, this paper has been studied as array antenna to increase the average gain.

### 3. ARRAY ANTENNA FOR MIMO SYSTEMS

#### 3.1 Array Antennas

The array antenna for MIMO systems can be shown in Figure 7. The array antenna works well in frequencies 1.85 – 3.51 GHz. Also, it is compact enough to be arranged to form the array having inter-element spacing of half wavelength.

#### 3.2 Simulation Results for Array antennas

The simulation results for array antenna indicated that the reflection coefficient of proposed antenna was reduced lower than -10 dB as shown in Fig.8. The isolation of the proposed antenna is shown in Fig.9.

According to simulation results, the Gain (dBi) in array antenna was higher than one antenna. The average gain of array antenna is 6.25 dBi. Also, to increase the number of antenna can increase the average gain. The proposed antenna is capable of WLAN (IEEE 802.11b/g), WiMAX (IEEE 802.16e) applications.

The simulated radiation pattern as E-plane and H-plane at 2 GHz, 2.5 GHz and 3 GHz are shown in Fig.10. According to the results, it was found that the simulated radiation pattern was in good agreement with the theory ones in the pattern of bi-directional.

## CONCLUSION

In this paper, the enhancement of bandwidth for rectangular slot antenna with L-shaped slot and double I shaped stub tuning has been studied and applying with array antenna for MIMO system. The simulation results indicated that the reflection coefficient ( $S_{11}$ ) of array antenna was reduced lower than -10 dB for application band (2 GHz -3 GHz). The simulated bandwidth of proposed antenna was 53.7% (1.88 - 3.26 GHz) which was pressed with the average gain value of 5.65 dBi.

## ACKNOWLEDGMENT

Thank you the department of Telecommunications Engineering, Faculty of Engineering and Architecture, Rajamangala University of Technology Isan for supporting the equipment and research funding.

## REFERENCES

Parkash D. and Khanna R., "Design of a dual band monopole antenna for WLAN / WiMAX applications," *Wireless And Optical Communication Networks (WOCN)*, pp.1 - 4, 2010.

Zhu C., Huang R. and Gong S. "Design of A Compact Triple-Band Antenna for Bluetooth/WLAN/WiMAX Applications," *10th International Symposium on Antennas, Propagation & EM Theory (ISAPE)*, 2012, pp. 183- 185, 22-26 October. 2012.

Kalraiya S., Singh H. S., Meshram M. K. and Thottapan M. "Microstripline-Fed Dual Band Printed Monopole Antenna for WLAN/WiMAX/HIPERLAN Applications," *Region 10 Symposium, 2014 IEEE*, pp. 224-227, 14-16 April 2014.

Jearapraditkul P., Kueathaweekun W., Anantrasirichai N., Sangarooand O., Wakabayashit T., "Bandwidth Enhancement of CPW-Fed Slot Antenna with Inset Tuning Stub", *International Symposium on Communications and Information Technologies, 2008. (ISCIT 2008)*, 21-23 Oct. 2008, pp. 14 -17.

Krishna D., Gopikrishna M., Anandan C. K., Mohanan P., and Vasudevan K., "CPW-Fed Koch Fractal Slot Antenna for WLAN/WiMAX Applications", *IEEE ANTENNAS AND WIRELESS PROPAGATION LETTERS*, VOL. 7, 2008.

Chaiboon P. and Namsang A. "Double Rectangular Grooves Microstrip Antenna With The Dual L-shape Tuning Stubs Supporting Tri-Band Frequencies",

*International Symposium on Antenna, Propagation ISAP 2010, Jeju, Jeju, Korea*, 25 - 28 October 2011

Chaiboon P., Namsang A., "Double Rectangular Grooves Microstrip Antenna With The Dual L-shape Tuning Stubs Supporting Tri-Band Frequencies", *International Symposium on Antennas and Propagation: ISAP 2011, Macao, China*, 23-26 November 2011.

Naktong W., Boonmaitree P., Kornsing S. and Ruengwaree A. "Quadruple Band Slot Antenna with Double L-Shaped Slot Etching Technique" *The 29th International Technical Conference on Circuit/Systems Computers and Communications (ITC-CSCC 2014)*, Phuket, Thailand, 1-4 July 2014.

Kaewchan B., Naktong W. and Ruengwaree A., "T-shape slot in rectangular slot antenna to enlarge bandwidth for broadband communication", *The 9<sup>th</sup> International Symposium on, Antennas, and EM Theory (ISAPE 2010)*, Guangzhou, China, 29-2 November 2010

Tunti-A-longkarn P. and Saleekaw S., "A Dual Wide Band CPW-fed Slot Antenna with Modified Coupling Slots", *IEEE International Conference on Computer Applications and Industrial Electronics (ICCAIE)*, 2011, pp. 309 - 314, 4 - 7 Dec 2011.

Zhang L., Jiao Y.-C., Ding Y., Chen B., and Weng Z.-B., "CPW-Fed Broadband Circularly Polarized Planar Monopole Antenna With Improved Ground-Plane Structure" *IEEE transactions on antennas and propagation*, Vol. 61, NO.9, September 2013 .

C. A. Balanis, *Antenna Theory*, 2<sup>nd</sup> Edition, New York, John Wiley & Son, Inc, 1982.

## NOMENCLATURE



**Apinya Innok** received the B.E. (2009), M.E. (2011), and D.E. (2013) degrees in the telecommunication engineering from Suranaree University of Technology. She is a Lecturer, Rajamangala University of Technology Isan. Her current interests include wireless communications and antenna applications.



**Watcharaphon Naktong** received the B.E. (2003), and M.E. (2011) degrees in electronics and telecommunication engineering from Rajamangala University of Technology Isan and Thanyaburi, respectively. He is Lecturer Rajamangala University of Technology Isan. His current interests include antenna design.



**Nuchanart Fhaffhiem** received the B.E. (2009), M.E. (2011), and D.E. (2014) degrees in telecommunication engineering from Suranaree University of Technology. She is a Lecturer, Rajamangala University of Technology Isan. Her current interests include antenna design, metamaterial and Electromagnetic Band Gap.