

# STUDY OF RECTANNA USING DIRECTIVE ANTENNA AT FREQUENCY OF 2.45 GHZ

Watcharaphon Naktong<sup>1</sup>, Nuchanart Fhaffhiem<sup>1</sup>, Apinya Innok<sup>1</sup>  
and Annoiy Ruengwaree<sup>2</sup>

<sup>1</sup>Department of Telecommunication Engineering, Faculty of Engineering and Architecture,  
Rajamangala University of Technology Isan (RMUTI), NakhonRatchasima, Thailand.

<sup>2</sup>Department of Electronics and Telecommunication Engineering, Faculty of Engineering,  
Rajamangala University of Technology Thanyaburi (RMUTT), Pathumthani, Thailand.

email: nuchanart.fa@gmail.com

**ABSTRACT** The popularly renewable energy is the wireless power transmission which the electromagnetic wave is transformed to electric energy at 2.45 GHz. This research studies the directive antennas which are rectangular waveguide antenna, cylindrical waveguide antenna, yagi-uda antenna and microstrip antenna, what the best of four antennas type can be transformed electromagnetic wave to electric power. The designed antennas are simulated by using computer simulation technology (CST) to analyze the characteristic, and then, the antenna prototype is fabricated. Secondary, we design the rectification prototype, it performed alternative-current (AC) Circuits to direct-current (DC) Circuits as shown the transformed energy system. The experimental results shows that a rectangular waveguide antenna can transform the most electric energy as voltage and current of 642 mV and 4.71  $\mu$ A, respectively with distance between transmitted antenna and rectenna around 2 – 3 m.

## 1. INTRODUCTION

In Thailand and other countries, renewable energy is extensively used such as solar cell, wind turbine, water-power, and so on. One of popularly renewable energy is the electromagnetic wave which is transformed to electric energy because of the wireless power is used in many public places (Takhedmit H., et al., 2009), (Young-Ho Suh, et al., 2002) and (Ramesh G.P. and Rajan A., 2014). Basically rectenna element consists of an antenna, impedance matching and filtering, rectification and load (Shuai Ji, et al., 2014). An antenna as it is popularly known component in the function blocks of the rectenna circuit (Jouko Heikkinen, et al.,

2000). Various kinds of rectennas have been demonstrated since Jouko and et al. presented the three planar rectennas on different PCB materials with 70 conversion efficiency at 2.45 GHz (Moorth M.R., et al., 2013). In wireless power transmission, the propagation wave is mostly propagated with omnidirectional radiation pattern and an antenna in the rectenna circuit should be directional antenna to direct the receiving pattern to wireless transmission.

This paper studies the directive antennas which are rectangular waveguide antenna, cylindrical waveguide antenna, yagi-uda antenna and patch microstrip antenna and we focuses on what the best of four antennas type can be transformed electromagnetic wave to electric power at 2.45 GHz as illustrated in Figure 1.




Fig. 1 Geometry for the rectenna system consisting of wireless transmission, directive antennas, and rectification circuit.

## 2. RECTANNA DESIGN

Let us consider geometry for the rectenna system that consists of transmitting power and rectenna. In this design, the directive antennas and rectifier circuits were all first designed, fabricated, and characterized separately.




Fig. 2 Directive antennas (a) rectangular waveguide (b) cylindrical waveguide (c) Yagi-Uda and (d) patch microstrip antenna




Fig. 3  $S_{11}$  (a) Rectangular waveguide (b) Cylindrical waveguide (c) Yagi-Uda and (d) Patch microstrip antenna.

Then they were combined to realize a complete rectennas. In this research each of directive antennas is used to test the conversion efficiency form wireless transmission at frequency of 2.45 GHz.

### 2.1 Directive Antenna Design

Figure 2 shows the antenna designs that are rectangular waveguide antenna, cylindrical waveguide antenna, Yagi-Uda antenna and patch microstrip antenna (Balanis, 1982) together with the dimensions of the 50- $\Omega$  matching antennas are illustrated.

From the design, the prototype antennas is fabricated and measured as shown along with Figure 2. Rectangular and cylindrical waveguide antennas are fabricated on aluminium and feeding system by using a  $\lambda/4$  wire probe connected with SMA connector. In addition, Yagi-Uda is constructed on cooper wire, consisting of driven, director and reflector. Moreover, patch microstrip antenna is fabricated on 1.6-mm-thick FR-4 substrate with a relative dielectric constant of 4.4 in the z-direction of the material. This measurement in  $S_{11}$  corresponds to improved power transmitting efficiency at 2.45 GHz. Let us consider in Table 1, there are measurement results of antenna prototypes. The rectangular waveguide antenna has the most directive gain of 8.92 dBi, so it is probable

the best converter to convert the electromagnetic wave. In Fig. 5 the radiation patterns of antennas are illustrated, it is directional radiation pattern.

Table 1 Directive antenna characteristics.

Antenna	Characteristics	Measurement Results
Rectangular waveguide antenna	$S_{11}$ (dB)	-26.92
	VSWR	1.09:1
	$Z_{in}$ ( $\Omega$ )	48.22+j4.17
	Gain (dBi)	8.92
Cylindrical Waveguide antenna	$S_{11}$ (dB)	-33.66
	VSWR	1.04:1
	$Z_{in}$ ( $\Omega$ )	50.58+j1.99
	Gain (dBi)	7.42
Yagi-Uda antenna	$S_{11}$ (dB)	-22.82
	VSWR	1.2:1
	$Z_{in}$ ( $\Omega$ )	52.44+j11.48
	Gain (dBi)	3.24
Patch Microstrip antenna	$S_{11}$ (dB)	-18.20
	VSWR	1.28:1
	$Z_{in}$ ( $\Omega$ )	42.30+j7.20
	Gain (dBi)	3




Fig. 4 Radiation pattern (a) Rectangular waveguide (b) Cylindrical waveguide (c) Yagi-Uda and (d) Patch microstrip antenna.

## 2.2 Rectification Circuit

Voltage multiplier circuit is used to supply a DC voltage with higher voltage and the load current is low, regardless of the output voltage to the load too much. The principle of this circuit is to use a capacitor, which is charged and discharged receiver in each half cycle of AC voltage. The output voltage is the summation of the voltage that across the capacitor to the input voltage. The initial circuit of increasing the voltage is included diode and capacitor in series with the AC input voltage. Hence, the voltage multiplier circuit is the better choice to design the rectifier as shown in Fig. 5 (Bin Alam, S., et al., 2013).






Fig. 5 Voltage multiplier circuit.

## 3. EXPERIMENTAL RESULTS

Since this work is measured the receiving power is plotted in Fig. 6 when the transmitting power is propagated from access point at frequency of 2.45 GHz. The distance between access point and rectenna is around 2-3 m as shown in Fig. 1. The experimental research confirmed that the rectenna by using a rectangular waveguide connecting with the voltage multiplier circuit can be transformed the electromagnetic wave to electric power of 642 mV, 4.71  $\mu$ A, and 3.02 mW.



(a)



(b)

Fig. 6 Measurement results of electric power.

## CONCLUSION

In this paper, RF to DC voltage and power conversion by using directive rectennas receiving has been discussed. When the high gain rectenna is used, the output electric power is high. In wireless transmission at 2.45 GHz case, a rectangular waveguide rectenna can be converted the electromagnetic power to voltage of 642 mV and current of 4.71  $\mu$ A. Second, a cylindrical waveguide rectenna can be converted the electromagnetic power to 451 mV and 3.37  $\mu$ A. Third, a Yagi-Uda rectenna can be converted the electromagnetic power to 198 mV and 1.59  $\mu$ A. Finally, a patch microstrip rectenna is the worst, it can be converted the electromagnetic power to 124 mV and 1.22  $\mu$ A.

## ACKNOWLEDGEMENT

The authors gratefully acknowledge simulation CST software support for this research project from the Department of Electronics and Telecommunication Engineering, Faculty of Engineering, Rajamangala University of Technology Thanyaburi (RMUTT), Pathumthani, Thailand. Moreover, thank you the department of Telecommunications Engineering, Faculty of Engineering and Architecture, Rajamangala University of Technology Isan for supporting the equipment and research funding.

## REFERENCES

- Takhedmit, H., Merabet, B., Merabet, B., Allard, B., Costa, F., Vollaïre, C. and Picon, O., Design of a 2.45 GHz rectenna using a global analysis technique, *3rd European Conference on Antennas and Propagation*, pp. 2321-2325, 2009.
- Young-Ho Suh and Kai Chang, A high-efficiency dual-frequency rectenna for 2.45- and 5.8-GHz wireless power transmission, *IEEE Transactions on Microwave Theory and Techniques*, vol. 50, pp. 1784-1789, 2002.
- Ramesh, G.P. and Rajan, A., Microstrip antenna designs for RF energy harvesting, *International Conference on Communications and Signal Processing*, pp. 1653-1657, 2014.
- Shuai Ji, Hua Qi, and Huifeng Zhang, Rectenna serves 2.45-GHz wireless power transmission, *Microwaves and RF*, 2014.
- Heikkinen, J., Salonen, P., and Kivikoski, M., Planar rectennas for 2.45 GHz wireless power transfer, *IEEE Radio and Wireless Conference*, pp. 63-66, 2000.
- Moorthi, M.R. and Saravanakumar, A., Rectenna model for 2.45GHz microwave wireless power transmission, *International Conference on Energy Efficient Technologies for Sustainability*, pp. 1360-1364, 2013.
- C.A. Balanis, "Antenna Theory Analysis and Design," Harper & Row Publishers, Newyork, 1982.
- Bin Alam, S., Ullah, M.S., and Moury, S., Design of a low power 2.45 GHz RF energy harvesting circuit for rectenna, *International Conference on Informatics, Electronics & Vision*, pp. 1-4, 2013.



**Watcharaphon Naktong** received the B.Eng. (2003), and M.Eng. (2011) degrees in electronics and telecommunication engineering from Rajamangala University of Technology Thanyaburi. He is Lecturer Rajamangala University of Technology Isan. His current interests include antenna design.



**Nuchanart Phafhiem** received the B.Eng. (2009), M.Eng. (2011), and D.Eng. (2014) degrees in telecommunication engineering from Suranaree University of Technology. She is a Lecturer, Rajamangala University of Technology Isan. Her current interests include antenna design, metamaterial and Electromagnetic Band Gap.



**Apinya Innok** received the B.E. (2009), M.E. (2011), and D.E. (2013) degrees in the telecommunication engineering from Suranaree University of Technology. She is a Lecturer, Rajamangala University of Technology Isan. Her current interests include wireless communications and antenna applications.



**Amnoiy Ruengwaree** received the Dr. Ing (Electrical Engineering) (2008) degrees from Kassel University, Germany. He is a Lecturer, Department of Electronics and Telecommunication Engineering, Faculty of Engineering, Rajamangala University of Technology Thanyaburi (RMUTT), Pathumthani, Thailand. His current interests include Ultra Wideband Radar System, Ultra Fast Electrical Pulse Generator, and Antenna Design.